

The Runco Crystal Series CX-OPAL42 LCD display with Optical Path ALignment (OPAL) technology is perfect for those who demand stellar image performance with the absolute latest features and elegant design.



<b>Native Resolution:</b>	1920 x 1080
<b>Screen Size:</b>	42" diagonal
<b>Screen Aspect Ratio:</b>	16x9
<b>Available Aspect Ratios:</b>	4:3, Letterbox, 16:9 Anamorphic, VirtualWide™
<b>DTV Compatibility:</b>	480i, 480p, 576p, 720p, 1080i, 1080p (24, 50, 60 Hz)
<b>Contrast Ratio:</b>	4000:1*
<b>Response Time:</b>	< 4mps
<b>Data/Graphics Compatibility:</b>	Up to 1600 x1200
<b>ISF Settings:</b>	Yes
<b>Vivix Processing:</b>	RTR™: Real Time Refresh 120Hz panel and processing, Vivix III 3:2 pulldown
<b>Inputs:</b>	(4) HDMI 1.3a, (2) Composite w/ L+R Audio, (1) S-Video w/L+R Audio, (2) Component w/ L+R Audio, (1) PC (HD15), (1) RS-232, (1) 3.5mm Wired Remote Input, (1) TosLink Optical Audio, (1) SCART (via Component + Composite)
<b>Outputs:</b>	n/a
<b>Audio System:</b>	10W x 2 audio amplification (speakers not included)
<b>Tuner:</b>	n/a
<b>Discreet IR:</b>	Full discrete remote control, Front and Rear IR windows
<b>Power Consumption:</b>	130W typical
<b>Power Requirements:</b>	100-240V AC, 50/60Hz
<b>Operating Environment:</b>	40 to 95°F (5 to 35°C); 20-80% humidity (non-condensing)
<b>Dimensions: (without stand)</b>	Width: 40 in. (1016 mm) Depth: 4.7 in (119.5 mm) Height: 24 in. (609 mm) <b>Weight:</b> 66lbs (30Kg) without stand
<b>Regulatory Approvals:</b>	Complies with FCC Class B, CE, C-Tick
<b>Limited Warranty:</b>	Two years parts and labor from the date of shipment from Runco. RuncoCare™ and Runco RedCarpet™ plans are also available.
<b>Ships with:</b>	Power cords (US, EU), remote control and two batteries (AAA), warranty information and registration card, owner's operating manual, cable ties.

\*Standard contrast ratio is measured in a completely darkened room. The contrast ratio of CX-OPAL42 in high ambient light is 300% greater than standard LCD in similar environment.